

**ELEKTRIC DUCT HEATER**

- Provided with overheat protection, limit thermostat auto reset(50°C) and manual reset(100°C) till 3kW 1F in main current, otherwise in control current
- Diameters, Ø100,Ø125,Ø160,Ø200,Ø250,Ø315,Ø355,Ø400mm
- Including CE marking and tagplate with electrical data and location code
- Min. air flow: Ø100 40m³/u, Ø125 70m³/u, Ø160 110m³/u, Ø200 170m³/u
- Min. air flow: Ø250 270m³/u, Ø315 415m³/u, Ø400 690m³/u
- Minimum airflow 1,6 m/sec.
- Material: galvanized steel / aluzinc
- Classification IP 44
- According to EN 60335-1, EN 60335-2-30, EN 60204-1
- Other dimensions,executions, power and voltage possible ask for the possibility and best prices.



TYPE: OMH-G												
(mm)	(kW)	(V)	art.	(mm)	(kW)	(V)	art.	(mm)	(kW)	(V)	art.	
Ø100	0,3	1x230	100335	Ø200	1	1x230	100354	Ø315	1	1x230	100373	
Ø100	0,5	1x230	102599	Ø200	1,2	1x230	100355	Ø315	1,2	1x230	100374	
Ø100	0,6	1x230	100336	Ø200	1,5	1x230	102565	Ø315	1,5	1x230	102505	
Ø100	0,9	1x230	100337	Ø200	2	1x230	100356	Ø315	2	1x230	100375	
Ø100	1	1x230	102594	Ø200	2,4	1x230	100357	Ø315	2,4	1x230	100376	
Ø100	1,2	1x230	100338	Ø200	3	1x230	100358	Ø315	3	1x230	100377	
Ø100	1,5	1x230	104977	Ø200	3	2x400	100359	Ø315	3	2x400	100378	
Ø125	0,3	1x230	100339	Ø200	5	2x400	102959	Ø315	5	2x400	100379	
Ø125	0,5	1x230	104978	Ø200	6	2x400	100360	Ø315	6	2x400	100380	
Ø125	0,6	1x230	100340	Ø200	6	3x400	100361	Ø315	6	3x400	100381	
Ø125	0,9	1x230	100341	Ø250	1	1x230	100362	Ø315	9	3x400	100382	
Ø125	1	1x230	104389	Ø250	1,2	1x230	100363	Ø315	12	3x400	100383	
Ø125	1,2	1x230	100342	Ø250	1,5	1x230	104981	Ø355	6	3x400	106801	
Ø125	1,5	1x230	100343	Ø250	2	1x230	100364	Ø400	3	2x400	100384	
Ø125	1,8	1x230	100344	Ø250	2,4	1x230	100365	Ø400	5	2x400	100385	
Ø160	0,5	1x230	100689	Ø250	3	1x230	100366	Ø400	6	2x400	100386	
Ø160	1	1x230	100345	Ø250	3	2x400	100367	Ø400	6	3x400	100387	
Ø160	1,2	1x230	100346	Ø250	5	2x400	100368	Ø400	9	3x400	100388	
Ø160	1,5	1x230	101880	Ø250	6	2x400	100369	Ø400	12	3x400	100389	
Ø160	1,75	1x230	106712	Ø250	6	3x400	100370	Ø400	15	3x400	100390	
Ø160	2	1x230	100347	Ø250	9	3x400	100371					
Ø160	2,4	1x230	100348	Ø250	12	3x400	100372					
Ø160	3	1x230	100349	Controller 16A, REG 16 230V/400V (till 6,4A 400V)								102945
Ø160	3	2x400	100350	Controller type 15.1 (till 15 kW)								106330
Ø160	3	3x400	104979	Controller type 15,1 P (till 27 kW)								106799
Ø160	5	2x400	100351	optional with control thermostat 0-40°C, 0-90°C, 1P								
Ø160	6	2x400	100352	optional with control thermostat 0-40°C, 30-85°C, 3P								
Ø160	6	3x400	100353									

