

Marine Heater - T2RIB



Offshore and marine heater with on/off-switch, thermostat and overheat protection. **IP 44** classified, the T2RIB is a splashproof, rust-proof electric heater designed for use in damp accommodation such as bathrooms and WCs.

A powerhouse in a small frame, the T2RIB 16 offers an output of 1600W from an area of less than 2 sq. ft., while the surface temperature remains below the maximum limit stipulated for electric heaters. The heater features a grille at the top to prevent it from being covered, and an automatic thermal cut-out to avert overheating. Constructed in aluminium and stainless steel, the lightweight T2RIB is ideal for ships and offshore installations which impose space and weight limitations.

T2RIB is designed to be fitted as fixtures and must be installed in a horizontal position

T2RIB heaters are approved by Det norske Veritas og American Bureau of Shipping. The heater also comes in a special version approved by Germanischer Lloyd

Type	Elnumber 230 V	Elnumber 400 V	Power	Height incl. grille	Height	Length	Depth
Standard version - approved by Norske Veritas:							
T2RIB 025	54 494 56	54 494 57	250 W	238 mm	150 mm	379 mm	96 mm
T2RIB 03	54 494 60	54 494 61	300 W	238 mm	150 mm	379 mm	96 mm
T2RIB 04	54 494 64	54 494 65	400 W	238 mm	150 mm	379 mm	96 mm
T2RIB 08	54 494 68	54 494 69	800 W	238 mm	150 mm	629 mm	96 mm
T2RIB 12	54 494 72	54 494 73	1200 W	238 mm	150 mm	869 mm	96 mm
T2RIB 16	54 494 76	54 494 77	1600 W	238 mm	150 mm	1134 mm	96 mm
T2RIB 20	54 494 90	54 494 91	2000 W	238 mm	150 mm	1395 mm	96 mm
GL-version - approved by Germanischer Lloyd:							
T2RIB 025	54 494 30	54 494 31	250 W	238 mm	150 mm	380 mm	96 mm
T2RIB 03	54 494 34	54 494 35	300 W	238 mm	150 mm	450 mm	96 mm
T2RIB 04	54 494 38	54 494 39	400 W	238 mm	150 mm	450 mm	96 mm
T2RIB 08	54 494 42	54 494 43	800 W	238 mm	150 mm	840 mm	96 mm
T2RIB 12	54 494 46	54 494 47	1200 W	238 mm	150 mm	1380 mm	96 mm
T2RIB 16	54 494 50	54 494 51	1600 W	238 mm	150 mm	1920 mm	96 mm

Specifications	
Flow-through marine heater with on/off switch, bi-metal thermostat , thermal cut-out and protection grille.	
230 V and 400V	
Colour: Pearl white	
Connection: Right-hand side	
Fitting to walls: Heaters must be fitted horizontally and are delivered with solid wall brackets.	
Max. surface temperature: 84°C	
Classification: IP 44. This heater is particularly suited for use in damp environment, e.g. bathrooms and toilets	
Installation distance requirements	T2RIB
Minimum distance to side wall:	2 cm
Minimum distance to floor:	2 cm
Minimum distance to ceiling or window sill:	38 cm